SPECIFICATIONS

Parameter Details (mm)	
Overall machine size (mm)	2870*1100*2200
Operating weight (kg)	1500
Track ground length (mm)	1350
Track width (mm)	180
Performance parameter (mm)	
Maximum digging depth (mm)	1800
Maximum unloading height(mm)	1850
Maximum excavation height (mm)	2580
Maximum Digging Radius （mm）	2900
Gradeability	30°
Walking speed (kmyh)	0-2.5
Bucket digging force (kn)	15
Dozer Height (mm)	300
Bucket capacity (m°)	0.025
Engine	
Engine type	B & S/koop192F/Kubota D722/Laidong385
Engine Cylinders	Single/Single/Triple/Triple
Horsepower （HP）	13.5/11/15/25
Fuel Type	Gasoline/Diesel/Diesel/Diesel

CARTIWELL

SHANDONG CARTI MACHINERY CO., LTD
TEL:+86 0537-2330670
FAX:+86 0537-2330670
EMAIL: CARTIWELL@126.COM
Add: jining High-tech zone, shandong Province, China

GET THE 1YR/1000HR FREE SERVICE

ORIGINAL CARTIWELL TOOL BAG
For maximum performance durability and safety

Note: ue to technological upgrades, the actual product maybediferent from what is shown. Diagrams, photos, and infor-mationare for reference only

CARTIWELL

PRODUCT | SIMPLE AND FLEXIBLE ALL-TERRAIN APPLICATION

CW-16PLUS



Operating weight:1500kg
Maximum digging depth:1800mm
Track width: 180mm

ISO CE EPA EURO5

When space is at a premium, the cw-16plus delivers the maneuverability, power, performance and versatility that get the job done.

When you have to take on a tough job in a tight space, look no further than the versatile CW-16plus. This compact excavator delivers the power you need, thecontrol you want, and the smooth performance you demand. Plus, CARTIWELL has improved the pump capacity, extended the dozer arm, and loaded it witha host of other upgrades that will help you get the job done more efficiently and more productively.

COLORS AND ACCESSORIES CAN BE CUSTOMIZED

CW-16PLUS



Strong engine power

We've upgraded the engine.so the CW16plus delivers more ofthe power and dependabilityyour work requires.in additionto its superior horsepower andperformance, it also offersow noise and vibration levels,exceptional fuel efficiency, and itis the EPA's certificated.

Improved pump capacity

We have increased the capacity of the hydraulic pump to provide you with the versatility you need to undertake all kinds of work.

Extended dozerarm

Cartiwell has extended the dozer arm to optimize theclearance between the dozer and the bucket--this makes collecting soil and rocks close to the machine simpleand more efficient. And, the extended length of the dozerarm also helps prevent soil or rocks from getting caught between the dozer and the crawler.

Optional engine,
KOOP 192 / Briggs & Stratton
KUBOTA / LAIDONG 385

Free choice of canopy or cab

The cab has a humanized design, a novel appearance and a wide field of vision. You can choose a cab according to your needs.





YOU CAN CHOOSE THE CANOPY OR CAB ACCORDING TO YOUR OWN NEEDS

- **One Year Warranty For the whole machine**
- **Provide free technical guidance.**
- **Contact us for machine price**

360° DIRECTION ROTATION

The cw-16plus mini excavator supports 360° body rotation and shakes the handle to control the construction direction to improve your construction quality.

30% OFF discount



- ***Hydraulic special valve***



- ***Hydraulic cylinder***





CW-16PLUS

From excellent lifting capacity to incredible operator comfort, CW-16plus helps you improve your work efficiency.



Rubber tracks

Rubber track can better adapt to all kinds of complex terrain, such as high altitude, narrow or uneven ground, which makes the excavator perform well even in limited construction environment. The flexibility of rubber crawler can absorb some vibration and noise, which makes the excavator more stable and quiet in the operation process.

hydraulic pressure system

The hydraulic transmission system has the characteristic of high transmission efficiency, which can fully utilize the power of the engine.



ANALYSIS OF CAB FUNCTIONS.

High-back suspension seat

The cw-16plus deluxe high-back seat increases productivity byproviding optimum comfort for operators of all sizes



Two-patternSelection System

The function of shaking the operating handle is mainly to control the movement, rotation, grasping and arm movements of the excavator, and the driver needs to master the operating mode of the handle skillfully.

Wrist rests

Adjustable wrist rests help reduce arm movement andincrease operator comfort for greater work efficiency

Folding pedal



Wider foot area

More spacious than many conventional tail-swinoexcavators, the cw-16plus wider foot area enhancesoperator comfort. The result is less operator fatigueand greater job efficiency



throttle lever

Locate the throttle lever, which should look as shown. Hold itsend, hold down the button located on top, and push the leveraway from you.



Power Switch

Locate the red power switch on your left near the seat. Turnwhile pulling the switch in the direction indicated by the labelaround it.



SAFE&RELIABLE

STURDY METAL

CUSTOMIZED