Parameter	Value
Model	H180T
Engine Options	Kubota D1105 / Kubota D1505
Rated Load	800Kg
Max. load capacity of the main arm	1000Kg
Extend the forearm for maximum load capacity	600Kg
Net weight of the vehicle body	2100Kg
Articulated turning angle	45°
Emission Standard	Euro V/ EPA Tier 4
Climbing height	30%
Hydraulic oil tank capacity	30L
Diesel tank capacity	30L
Total length of vehicle body	4430mm
Wheel spacing	1550mm
Lowest point bucket angle	51°
Max. unloading height before extension	2215mm
Max. unloading height after extension	2825mm
Highest point bucket height	4035mm
Highest point bucket angle	51°
Safe distance for unloading after extension	1350mm
Total width of wheels	1046mm
The highest unloading angle	31°
Safe distance for unloading before extension	830mm
Ground clearance	242mm
Excavation depth	120mm
Speed	12km/h

CARTIWELL

SHANDONG CARTI MACHINERY CO., LTD

TEL:+86 0537-2330670

FAX:+86 0537-2330670

EMAIL: CARTIWELL@126.COM

Add: jining High-tech zone, shandong Province, China

GET THE 1YR/1000HR FREE SERVICE

ORIGINAL CARTIWELL TOOL BAG

For maximum performance durability and safety

Note: ue to technological upgrades, the actual product maybediferent from what is shown. Diagrams, photos, and infor-mationare for reference only

HONESTY CREATES THE FUTURE
QUALITY CREATES BRILLIANCE

CARTIWELL

CARTIWELL COMPACT WHEEL LOADER

H180

H130 supports quick replacement of multiple attachments. It can operate flexibly in confined spaces and handle loading, excavation, snow removal and site leveling.



Sturdy telescopic arm

The telescopic boom is built to be sturdy andstable. The parallel motion takes place hy-draulically. All important hydraulic lines areinside and are protected against external in-fluences.



EXCELLENT PERFORMANCE MULTIPLE ATTACHMENTS

1. The legendary **articulated swing joint** Allfour wheels arein constant contact withthe ground and the machine moveswith maximum traction.

2. Two larger and stronger **lifting cylinders** ensure that the load distribution is always transmitted to the loading arm optimally, providing the lifting power for the boom.

3. Strong **steel structure**, durable and easy to maintain, thick welded steel frame and reinforced boom, impact resistance, long-term heavy load without deformation.


Standard with bucket

Thickened wear-resistant bucket with detachable teeth can be equipped with accessories such as snow shovel, digging bucket and standard bucket.

Deep tooth cross-country tire

Deep lug agricultural tires provide outstanding grip. Anti-slip performance on mud, sand and uneven ground.





POWER
KUBOTA
DIESEL ENGINE

Low Fuel Consumption Heavy Duty Diesel Genset, Adapt to harsh working conditions







Shock-absorbing seat



illuminating system

Steering Wheel

H180 WHEEL LOADER

Specifications, logos and shell colors can be customized, we will provide you with the best solution.